

STA-450D - Amplifier



4-channel digital amplifier

- Class D concept
- Silent operation due to fanless cooling concept
- 8 Ohm bridged operation possible
- Mute function for each channel
- 4 level controls
- 1 LED per channel for indicating overload (clip)
- Protected against short circuit

Teknisk Data

Channels	: 4
Zones	: -
Power rating	: -
Power rating at 2 Ohm	: -
Power rating at 4 Ohm	: 4 x 50 W
Power rating at 8 Ohm	: 4 x 30 W
Power rating at 100 V	: -
Power rating with 4 Ohm bridged operation	: -
Power rating with 8 Ohm bridged operation	: 2 x 100 W
Peak music power output (P _{MAX})	: 300 W
Output impedance	: -
Inputs	: 1 V/20 k Ohm unbal.550 mV/20 k Ohm bal.
Dampening factor	:
Frequency range	: 10-20,000 Hz
Crossover network	: -
Crossover frequency	: -
Integrated limiter	: -
Equalizer bass	: -
Equalizer midrange	: -
Equalizer treble	: -
S/N ratio	: -
Crosstalk attenuation	: ? 45 dB
THD	: -
Power supply	: ~ 230 V/50 Hz/300 VA
Mains voltage	: ~ 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 300 VA
Power consumption, standby	: -
Standby current	: -
Alternative operating voltage	: -
Alternative power supply	: -
Admiss. ambient temp.	: 0-40 Â°C
Dimensions	: 483 x 90 x 330 mm, 2 RS
Width	: ~ 483 mm
Height	: 90 mm

Depth	: 330 mm
Rack spaces, RS	: 2
Weight	: 7.2 kg
Connections	: 4 x XLR, bal.4 x RCA4 x spring-load. speaker term. L/R