

PAB-58/SW - 2way Speaker Cabinet



This particularly attractive and efficient series of PA speaker systems is clearly designed for effective fixed installations, whether in restaurants and bars, hotels, for background PA applications at sport facilities, PA applications in adjoining rooms at discotheques or at conferences: these PAB speaker systems offer a perfect price-performance ratio and a high quality. Pair of high-quality PA speakers, 50 WMAX, 8 Ohm

- 2-way speaker systems in an ABS cabinet which is both functional and at the same time of an attractive appearance
- Polypropylene bass speaker and dome tweeter with horn front attachment (waveguide)
- High-quality crossover networks with a perfect long-term stability, e.g. due to consistently applying film capacitors
- Impress by a really fast and brilliant sound of high efficiency and a high dynamic range and are particularly optimised for PA applications of modern music of higher volume levels
- Supplied with wall bracket

Teknisk Data

Active/passive	: passive
Operating voltage	: -
Impedance	: 8 Ohm
Frequency range	: 75-22,000 Hz
Amplifier power	: -
Max. power	: -
THD	: -
S/N ratio	: -
Input signal	: -
System	: 2-way
Bass speaker	: polypropylene bass speaker
Midrange speaker	: -
Tweeter	: dome tweeter
Number of speakers	: 2
Speaker size	:
Power rating	: 30 W
Peak music power output	: 50 W
Sensitivity	: 92 dB/W/m
Max. rated SPL	: 107 dB
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Material (housing/cabinet)	: ABS plastic
Colour	: black
Mounting facility	: 2 x thread M6
Protected against ball rebound	: -
Protective class	: -
Admiss. ambient temp.	: 0-40 Å°C
Power supply	: -
Dimensions	: 160 x 250 x 150 mm
Width	: 160 mm
Height	: 250 mm
Depth	: 150 mm
Weight	: 2.2 kg
Inputs	: speaker screw terminal
Outputs	: -



CLW Media AB
Lyckerumsgatan 14
593 36 Västervik
0725710501
<https://www.strongvoice.se>

Other features

: -